



**Configuration:**

LA-504-01 Listen EVERYWHERE Replacement Power Supply (North America)\*

LA-504-02 Listen EVERYWHERE Replacement Power Supply (Asia, UK)\*

LA-504-03 Listen EVERYWHERE Replacement Power Supply (Euro)\*

LA-504-04 Listen EVERYWHERE Replacement Power Supply (Australia)\*

\*01, 02, 03, and 04 designation refers to international plug type (type B, G, C, and I) for the power supply.

**Product Overview:**

Compatible with our Listen Everywhere servers, the LA-504 replacement power supply has four different line cord configurations to allow for use in nearly any region of the world.

**Highlights:**

- Safe, reliable 5 VDC power for Listen Everywhere servers
- Available with four user-selectable line cord configurations for use in nearly any region

**Includes:**

One (1) Listen Everywhere Replacement Power Supply  
One (1) Line cord

Product Specification: Listen EVERYWHERE Replacement Power Supply	
<b>Power</b>	
Power Supply Input	100-240V, 50-60 Hz, 2.0A
Power Supply Output	5 VDC, 6.0A 30W
Power Supply Connector	.217 in (5.5mm) OD, .083 in (2.1 mm) ID, barrel type, center positive
Power Supply Type	In Line
<b>Physical</b>	
Color	Black
Cable Length	Power Supply Cable: 4.0 ft. (122 cm), IEC Line Cord: 6.0 ft. (183 cm)
Dimensions (H x W x D)	1.5 in. x 2.00 in. x 4.5 in. (38 mm x 51 mm x 115 mm)
Weight	(-01) 12.8 oz. (300 g), (-02) 16 oz. (500 g), (-03) 16 oz. (500 g), (-04) 12.8 oz. (400 g)
<b>Environmental</b>	

Product Specification: Listen EVERYWHERE Replacement Power Supply	
Temperature - Operation	-10 °C (14 °F) to +40 (104 °F)
Temperature - Storage	-20 °C (-4 °F) to +50 (122 °F)
Relative Humidity	0 to 95% relative humidity, non-condensing
<b>Compliance</b>	
Power Supply Compliance	CUL, UL, CE, CCC, RCM, CCC, EAC, PSE, FCC, RoHS